

DEPARTMENT OF PUBLIC WORKS

DRIVEWAY CONSTRUCTION / ALTERATION PERMIT APPLICATION

\$20 Fee Paid	Permit #	Dig Safe#_	
☐ New Access	☐ Second Access	☐ Pave Existing	☐ Repair Existing
THIS APPLICATION IS REQ EXISTING TO INCLUDE PLA UNPAVED DRIVEWAYS.			PRIVEWAYS, OR ALTERATION OF RADES, OR PAVING OF
(Print) Property Owner's nam	e:		Date:
Property Address:			
Mail Address (if different):		Email:	
Map / Lot #:	Phone#: ()	, Cell#	: ()
Contractor Name:		Approx. S	tart Date:
Phone#: ()	, Cell#: ()		

Property owner hereby agrees to construct an access (driveway) in accordance with all current Town/ State regulations.

Per the Town's Minimum Road Standards, all new driveways will have a minimum width of 12 feet and a maximum width of no more than 20 feet with 5 foot radii at the edge of pavement at the street. Radii shall be flared to allow proper drainage into any drainage ditches along the roadway. Commercial and industrial driveways shall have a minimum width of 20 feet.

All driveways shall be located a minimum of 15 feet from all side and rear property lines. A <u>paved</u> apron of at least 10 feet is required, upon completion. A temporary stabilized construction entrance shall be maintained throughout construction, to limit tracking onto public roadway.

The proposed driveway is to have proper site distance of a minimum of 250 feet in all directions and all seasons to ensure safety of access and exit to the property served. Commercial and industrial driveways shall have a proper sight distance of a minimum of 365 feet in all directions and all seasons.

No obstructions are allowed within the Town's right-of-way other than mailboxes. <u>Shrubs, trees, markers, stones, manmade items and other structures shall be outside of the right of way unless specific permission is gained from the Town prior to placement.</u>

Owner shall NOT obstruct the natural flow of water along roadside, in any way whatsoever, and when directed by the Department of Public Works will provide a culvert in proper placement within the ditch line per the Town's Minimum Road Standards, and as sized by the Town. Maintenance and upkeep of same is the responsibility of the property owner as per RSA 236:13, VI.

The finished surface of the access will slope away from the existing town road at a minimum pitch of 1 inch per foot for a minimum of 4 feet before rising with land.

distances. Additional sheets or plan may be attached.	(e.g. building w/ address, utility pole, roposed pavement materials and sight
*Defers heims annualized interest after contain of annual conditions	
*Before being approved, please stake center of proposed drive	way ii new.
ature on this application acknowledges adherence to the above criteri	a.
Signature of property owner / agent	 Date
DO NOT WRITE INSIDE THIS BOX	
DO NOT WRITE INSIDE THIS BOX ERMIT IS DENIED FOR THE FOLLOWING:	
ERMIT IS DENIED FOR THE FOLLOWING:	
ERMIT IS DENIED FOR THE FOLLOWING:	
ERMIT IS DENIED FOR THE FOLLOWING:	
ERMIT IS DENIED FOR THE FOLLOWING:	
ERMIT IS DENIED FOR THE FOLLOWING:	